

Alle Ladeangaben ohne Gewähr!

CALIBER	BULLET		Weight									Primer	POWDER		Charge	VELOCITY m/s			ENERGY joules			TRAJECTORY cm/m (muzzle -4.5 cm)					GEE		PACKING			
	Code	Type	Gr	Grs									Vihtavuori	Gramm/Grs		0	100	200	300	0	100	200	300	50	100	150	200	250	300	m		Box
22 PPC USA	111G	RACEHEAD		3.4	52	-	•	-	-	-	•	SR	N130	1.60/24.7	1035	900	775	655	1821	1377	1021	730	-0.3	1.4	0	-4.6	-13.5	-27.2	191	20	500	S HAMMERHEAD = SPBT Bonded core HAMMERHEAD = SP Bonded core POWERHEAD = Barnes-X® TWINHEAD = Nosler Partition® ARROWHEAD = Nosler Ballistic Tip® RAMHEAD = Barnes Solid® SPEEDHEAD = Full metal jacket GAMEHEAD = Soft point RANGE = Full metal jacket SUPER RANGE = Hollow point BT RACEHEAD = Sierra Match-King®
222 Rem	105G	SPEEDHEAD	+	3.2	50	•	•	-	-	•	SR	N120	1.25/19.3	975	800	638	515	1540	1028	660	428	0.4	2.1	0	-8.0	-21.3	-42.0	175	20	1000		
222 Rem	106G	GAMEHEAD		3.2	50	-	-	-	-	•	SR	N120	1.25/19.3	975	800	638	515	1540	1028	660	428	0.4	2.1	0	-8.0	-21.3	-42.0	175	20	1000		
222 Rem	110G	GAMEHEAD	+	3.56	55	-	-	-	-	•	SR	N130	1.40/21.6	1000	842	700	573	1780	1261	871	585	0.1	1.7	0	-5.9	-17.2	-34.4	181	20	1000		
222 Rem	482G	POWERHEAD		3.2	50	-	•	•	-	-	•	SR	N130	1.40/21.6	975	807	662	540	1540	1056	710	472	0.4	2.1	0	-6.6	-19.7	-39.0	177	20	1000	
222 Rem	111G	RACEHEAD		3.4	52	-	•	-	-	-	•	SR	N120	1.15/17.7	925	785	660	550	1455	1048	741	514	0.6	2.3	0	-7.0	-19.9	-39.4	172	20	1000	
222 Rem	105G	RANGE	+	3.2	50	•	•	-	-	-	•	SR	N120	1.25/19.3	975	800	638	515	1540	1028	660	428	0.4	2.1	0	-8.0	-21.3	-42.0	175	100	1000	
222 Rem Mag	105G	SPEEDHEAD	+	3.2	50	•	•	-	-	-	•	SR	N120	1.38/21.3	985	805	646	522	1572	1051	677	441	0.3	2.0	0	-7.8	-20.8	-40.9	177	20	1000	
222 Rem Mag	106G	GAMEHEAD	+	3.2	50	-	-	-	-	-	•	SR	N120	1.38/21.3	985	805	646	522	1572	1051	677	441	0.3	2.0	0	-7.8	-20.8	-40.9	177	20	1000	
222 Rem Mag	110G	GAMEHEAD	+	3.56	55	-	-	-	-	-	•	SR	N130	1.57/24.2	1015	855	711	584	1834	1301	901	607	0	1.6	0	-5.7	-16.5	-33.1	184	20	1000	
223 Rem	105G	SPEEDHEAD	+	3.2	50	•	•	•	-	-	•	SR	N120	1.40/21.6	985	805	646	522	1572	1051	677	441	0.3	2.0	0	-7.8	-20.8	-40.9	177	20	1000	
223 Rem	106G	GAMEHEAD	+	3.2	50	•	•	•	-	-	•	SR	N120	1.40/21.6	985	805	646	522	1572	1051	677	441	0.3	2.0	0	-7.8	-20.8	-40.9	177	20	1000	
223 Rem	110G	GAMEHEAD	+	3.56	55	-	-	-	-	-	•	SR	N130	1.57/24.2	1015	855	711	584	1834	1301	901	607	0	1.6	0	-5.7	-16.5	-33.1	184	20	1000	
22-250 Rem	105G	SPEEDHEAD	+	3.2	50	•	•	•	-	-	•	LR	N140	2.30/35.5	1150	950	776	623	2142	1461	976	630	-0.6	1.1	0	-4.4	-12.8	-26.3	199	20	500	
22-250 Rem	106G	GAMEHEAD	+	3.2	50	-	-	-	-	-	•	LR	N140	2.30/35.5	1150	950	776	623	2142	1461	976	630	-0.6	1.1	0	-4.4	-12.8	-26.3	199	20	500	
22-250 Rem	110G	GAMEHEAD	+	3.56	55	-	-	-	-	-	•	LR	N140	2.32/35.8	1115	945	790	651	2213	1590	1111	755	-0.6	1.1	0	-4.4	-12.7	-25.8	199	20	500	
6PPC USA	117E	RACEHEAD		4.5	70	-	•	-	-	-	•	SR	N130	1.65/25.4	945	825	715	610	2010	1532	1150	838	0.3	1.9	0	-6.0	-16.5	-32.9	178	20	500	
243 Win	114E	SPEEDHEAD	+	5.8	90	•	•	•	-	-	•	LR	N140	2.25/34.7	870	781	700	625	2195	1770	1421	1131	0.8	2.5	0	-6.9	-18.8	-36.2	171	20	500	
243 Win	112E	GAMEHEAD	+	5.8	90	-	-	-	-	-	•	LR	N160	2.95/45.5	955	861	775	695	2645	2148	1740	1398	0.2	1.8	0	-5.4	-14.8	-28.8	187	20	500	
243 Win	484E	POWERHEAD		5.5	85	-	-	-	-	-	•	LR	N160	3.05/47.1	980	898	820	747	2642	2217	1850	1534	-0.1	1.5	0	-4.8	-13.2	-25.7	194	20	500	
243 Win	121E	TWINHEAD		6.5	100	-	-	-	-	-	•	LR	N160	2.75/42.4	935	852	773	700	2840	2358	1944	1590	0.2	1.8	0	-5.5	-15.0	-29.2	185	20	500	
25-06 Rem	425E	TWINHEAD		7.5	115	-	-	-	-	-	•	LR	N160	2.95/45.5	910	829	753	681	3105	2579	2128	1740	0.4	1.9	0	-5.8	-16.0	-30.9	180	20	500	
25-06 Rem	125E	GAMEHEAD		7.6	117	-	-	-	-	-	•	LR	N160	2.95/45.5	910	829	753	681	3105	2579	2128	1740	0.4	1.9	0	-5.8	-16.0	-30.9	182	20	500	
6.5x55 SE	118E	SPEEDHEAD		6.5	100	•	•	•	-	-	•	LR	N160	3.00/46.3	800	682	576	480	2080	1514	1077	749	1.8	3.5	0	-9.8	-26.9	-53.1	152	20	500	
6.5x55 SE	119E	RACEHEAD		9.0	139	-	-	-	-	-	•	LR	N160	2.75/42.4	850	803	758	714	3251	2903	2587	2296	0.7	2.2	0	-6.2	-16.7	-31.7	175	20	500	
6.5x55 SE	120E	GAMEHEAD		10.1	156	-	-	-	-	-	•	LR	N160	2.70/41.7	800	720	644	574	3232	2616	2096	1662	1.4	3.1	0	-8.4	-22.7	-43.6	159	20	500	
6.5x55 SE	118E	RANGE		6.5	100	•	•	•	-	-	•	LR	N160	3.00/46.3	800	682	576	480	2080	1514	1077	749	1.8	3.5	0	-9.8	-26.9	-53.1	152	50	500	
270 Win	114B	SPEEDHEAD		8.4	130	•	•	•	-	-	•	LR	N140	3.00/46.3	860	755	658	568	3106	2394	1816	1356	0.9	2.6	0	-7.6	-20.8	-40.6	166	20	500	
270 Win	211B	HAMMERHEAD	+	10.1	156	-	-	-	-	-	•	LR	N160	3.37/52.0	840	745	660	581	3563	2805	2200	1705	1.2	2.8	0	-7.7	-21.1	-40.8	164	20	500	
7x33 Sako	108B	SPEEDHEAD	+	5.1	78	•	•	•	-	-	•	SR	N110	1.07/16.5	740	571	437	344	1396	832	487	303	3.6	5.9	0	-15.4	-43.9	-87.8	139	50	1000	
7x33 Sako	109B	GAMEHEAD		5.1	78	-	-	-	-	-	•	SR	N110	1.07/16.5	740	571	437	344	1396	832	487	303	3.6	5.9	0	-15.4	-43.9	-87.8	139	50	1000	
7x64	121B	GAMEHEAD		7.8	120	-	-	-	-	-	•	LR	N140	3.35/51.7	945	850	760	680	3483	2820	2255	1802	0.1	1.7	0	-5.5	-16.0	-30.7	185	20	500	
7x64	216B	HAMMERHEAD	+	11.0	170	-	-	-	-	-	•	LR	N160	3.40/52.5	850	775	705	640	3974	3304	2735	2255	0.9	2.4	0	-7.2	-19.2	-36.5	170	20	500	
7x65R	216B	HAMMERHEAD	+	11.0	170	-	-	-	-	-	•	LR	N160	3.30/50.9	800	728	662	599	3520	2917	2409	1976	1.4	3.1	0	-8.1	-21.8	-41.6	160	20	500	
7 mm Rem Mag	122B	GAMEHEAD		9.1	140	-	-	-	-	-	•	LRM	N160	4.00/61.7	960	886	815	750	4193	3570	3023	2552	0.0	1.6	0	-5.1	-13.7	-26.2	192	20	500	
7 mm Rem Mag	216B	HAMMERHEAD	+	11.0	170	-	-	-	-	-	•	LRM	N160	3.80/58.6	905	827	753	685	4505	3759	3121	2580	0.4	2.0	0	-5.9	-16.4	-31.4	180	20	500	
7.62x39	117A	SPEEDHEAD	+	8.0	123																											